REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	B	ECO-14760	08/14/2025	TDUFRENE	DGUST





PART NUMBER	LENGTH	
	FEET	METERS
TRD855HFO-1	1.0	0.30
TRD855HFO-2	2.0	0.61
TRD855HFO-3	3.0	0.91
TRD855HFO-5	5.0	1.52
TRD855HFO-7	7.0	2.13
TRD855HFO-10	10.0	3.05
TRD855HFO-15	15.0	4.57
TRD855HFO-20	20.0	6.10
TRD855HFO-25	25.0	7.62
TRD855HFO-30	30.0	9.14
TRD855HFO-40	40.0	12.19
TRD855HFO-50	50.0	15.24
TRD855HFO-60	60.0	18.29
TRD855HFO-75	75.0	22.86
TRD855HFO-100	100.0	30.48

NOTES:

1. MATERIAL:
   PLUG HOUSING: POLYCARBONATE, CLEAR, UL94V-0
   CONTACTS: PHOSPHOR BRONZE
   CABLE JACKET: HIGH FLEX, THERMOPLASTIC ELASTOMER, OIL, UV, AND WELD SPLATTER RESISTANT. COLOR, BLACK.
   PLUG SHIELDING: BRASS
   SNAGLESS BOOT: LSZH, BLACK

2. FINISH:
   CONTACTS: 50 µINCHES GOLD IN CONTACT AREA OVER 100 µINCHES NICKEL PLATE OVERALL
   PLUG SHIELDING: NICKEL PLATED

3. CABLE CHARACTERISTICS:
   SHIELDED, FOUR TWISTED PAIR, CAT 5E MODULAR CABLE
   CONDUCTORS: 26AWG STRANDED TINNED COPPER
   OVERALL SHIELD: 38AWG TINNED COPPER BRAID
   SECOND SHIELD OF ALUMINUM/ POLYESTER FOIL

4. MISCELLANEOUS:
   PLUG CONFORMS TO TIA-1096
   OPERATING TEMPERATURE RANGE: -40°C TO +75°C
   LENGTHS OVER 10 METERS (32.8 FT) ARE CHANNEL RATED.
   CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
   CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM PACKAGING SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:
EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION).

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:
.X = ±.2 [5]
.XX = ±.02 [0.5]
.XXX = ±.005 [0.13]
FRACTIONS ± 1/32
ANGLES ± 1°

CABLE LENGTH TOLERANCES:
≤12 [305] = +1 [25] / -0
>12 [305] ≤ 60 [1524] = +2 [51] / -0
>60 [1524] ≤ 120 [3048] = +4 [102] / -0
>120 [3048] ≤ 300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0

ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE.
UN-DIMENSIONED/NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION
COLORS MAY VARY

L-com®
an INFINITE brand
Website: www.L-com.com
Phone: 1.800.341.5266 | 1.978.682.6936

INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5

SCALE	SHEET
NONE	1 OF 1

DESCRIPTION
RJ45 C5e SFUTP TPE BLK HFX

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	43321	D.FRISIELLO	TRD855HFO	B

LC DS Rev-D4 Asize